

MTC-2438HQ3X

MTC-2438HQ3X



FEATURES



3D Free Rotation



Option:
MTB-201 Bracket

MTC-2438HQ3X new

- ◆ 1/3" Super Hi-Res. Dome Camera
- ◆ SONY HQ1/540TVL/0.25Lux@F1.2
- ◆ 10 Bit Digital Signal Processing
- ◆ Built-in Aspherical Lens
- ◆ AES/AGC/BLC/FL Switchable(ON/OFF)
- ◆ Unique 3 Axis Mechanism



Tol: ±0.5 Unit:mm

SPECIFICATIONS

| | MTC-2438HQ3X | |
|-------------------------|--|---------------|
| TV System | PAL | NTSC |
| Image Sensor | 1/3" SONY Color CCD | |
| Number of Total Pixels | 795(H)X596(V) | 811(H)X508(V) |
| Synchronizing System | Internal | |
| Resolution | 540 TVL | |
| Minimum Illumination | 0.25 Lux@F1.2 | |
| Signal to Noise Ratio | More Than 50 dB(AGC Off) | |
| Automatic Gain Control | ON/OFF (Switchable) | |
| F.L. (Flickerless) | ON/OFF (Switchable) | |
| AES | ON/OFF (Switchable) | |
| Back Light Compensation | ON/OFF (Switchable) | |
| DC Level | The VR for adjusting the IRIS level of auto Iris lens. | |
| White Balance | AWB | |
| Video Output | 1Vp-p Composite / 75 Ω | |
| Lens/Angle of view(H) | Standard:f2.9mm~10mm/F1.2 Aspherical Auto Iris Lens / 94.6° ~28.8° Option:f2.5mm~6.0mm/F1.3 Aspherical Auto Iris Lens / 108.2° ~47.6° | |
| Power Supply | Standard:12 Vdc; Option:12 Vdc/24 Vac | |
| Power Consumption | 2.0 W | |
| Operation Temperature | -10° C~+50 C° | |
| Operation Humidity | RH85% or less | |
| Storage Temperature | -20° ~60 C° | |
| Dimensions | 118(DIA) X 88(H) mm | |
| Weight | 12 Vdc: 300 g; 12 Vdc/24 Vac: 370 g | |